

# FTR 900

# FTR 900 Crew



FTR 900

## AUSTRALIA'S TOP SELLING TRUCK BRAND SINCE 1989.

## AT A GLANCE

**GVM** 15,000 kg **GCM** 24,000 kg\*\*

Power 191 kW @ 2,400 rpm

**Torque** 761 Nm @ 1,450 - 2,400 rpm

## **UPGRADE OPTIONS**

**Premium Pack:** Automated Manual Transmission (AMT), Auto control for air conditioning (except crew)

\*\* Refer to back page weights table for details.



## **ADVANCED TECHNOLOGY**

Emissions: Euro V / ADR 80/03 Meets EEV emissions standard

Driver and passenger airbag with seatbelt

pretensioner

ADR42 compliant sleeper with mattress -

except crew

ECE-R93 compliant front underun protection device (FUPD)

Anti-lock Braking System (ABS)

Hill Start Aid (HSA)
Electric mirrors

Electric mirrors

Electro-hydraulic cab tilt

Coil spring cab suspension (except crew)

Front and rear stabiliser bars

Cruise control

Isri 6860 seat with integrated seatbelt

Cornering lamps





# FTR Medium | Long | Crew

## DRIVELINE AND CHASSIS SPECIFICATIONS

## **ENGINE: SITEC SERIES III 255 (ISUZU 6HK1-TCC)**

**Type:** 6 cylinder 24 valve SOHC

**Displacement:** 7,790 cc **Compression Ratio:** 17.5:1

Bore x Stroke: 115 mm x 125 mm

Max power (DIN-NET): 191 kW (256 HP) @ 2,400 RPM

(JIS Gross): 198 kW (265 HP) @ 2,400 RPM

**Max torque (DIN-NET):** 761 Nm (561 lb.ft) @ 1,450 - 2,400 RPM

(JIS Gross): 788 Nm (581 lb.ft) @ 1,450 - 2,400 RPM Induction system: Electronically controlled variable nozzle turbocharger

with air-to-air intercooler.

**Fuel injection:** Direct injection high pressure common rail system. **Emission control system:** Cooled EGR with exhaust Diesel Particulate Diffuser (DPD). ADR 80/03 (Euro V) compliant. EEV compliant.

#### **CLUTCH**

#### Standard model:

- Air assisted hydraulic control. Single plate 381 mm diameter.
- Total lining area: 1,363 cm2

#### **Premium Pack:**

 Fully automated hydraulically controlled wet clutch and fluid coupling with lock up.

## **TRANSMISSION**

#### ISUZU MZW-6P

- Synchromesh on gears 2-6. Triple cone synchromesh on 2nd and 3rd gears. Integral oil pump provides full pressure lubrication.
- PTO provision on LHS of transmission case. PTO drive from mainshaft gear.
- Gear ratios (:1)

 1st
 2nd
 3rd
 4th
 5th
 6th
 Rev

 6.615
 4.095
 2.358
 1.531
 1.000
 0.722
 6.615

## Standard model:

. 6 speed manual with air assisted shift.

## Premium Pack:

 6 speed Automated Manual Transmission (AMT) with both fully automatic and clutchless manual operation modes.

#### **AXLES**

Front: Isuzu F063

• Reverse Elliot I-Beam. 6,300 kg capacity.

Rear: Isuzu R092

- Full floating Banjo type. 9,200 kg capacity.
- Drive ratio: 5.571:1

#### **SUSPENSION**

#### Front:


- Single stage alloy steel taper leaf springs.
- Double acting hydraulic shock absorbers. Stabiliser bar.

#### Rear

• Multi leaf main spring, multi leaf helper spring. Stabiliser bar.

#### **BRAKES**

- Dual circuit full air taper roller front and rear drum brakes.
- ABS.
- Hill Start Aid (HSA).
- Front drum size: 410 x 160 mm
- Rear drum size: 410 x 180 mm
- · Spring park brake.



- Air controlled exhaust brake.
- · Air dryer.

## **STEERING**

- Power assisted recirculating ball steering.
- Gear ratio: 22.4:1
- Turns lock to lock: 4.8
- Maximum angle: 49° (inside wheel) / 37° (outside wheel)

#### **WHEELS AND TYRES**

- 22.5 x 8.25 ten stud steel wheels.
- 275/70R22.5 148/145M Michelin XZE2 Tubeless.
- · Maximum tyre rating:

Steer axle: 6,300 kg Drive axle: 11,600 kg

Spare wheel and tyre assembly with winch type carrier.

## **CHASSIS FRAME**

- Cold rivetted ladder frame with parallel side rails. HT540A high tensile weldable steel sidemembers.
- Frame dimensions:

Side rail (mm): 254 x 85 x 8.0 Rear frame width (mm): 850

#### **FUEL TANK**

- Frame mounted 200L steel fuel tank.
- · Lockable fuel cap.

#### **ELECTRICAL SYSTEM**

- · 24 volt electrical system.
- Single cab: 60 amp alternator. Crew cab: 90 amp alternator.
- 24 Volt, 4.5 kW starter motor.

- 2 x 115E41L (651 CCA) batteries connected in series
- Underdash CAN interface unit and connector. SAE J1939 protocol.
   Facilitates connection to a Fleet Management System (FMS) (not supplied).

## CABIN SPECIFICATIONS AND APPOINTMENTS

#### **CAB EXTERIOR**

- All steel construction with electro-hydraulic cab tilt. High tensile steel used for cab underframe.
- Complies with ECE-R29 cab strength standard.
- Single cab: Full floating cab with coil spring suspension.
   Crew cab: Rubber cab mounts.
- · Heavy duty non slip entry steps.
- 90° opening internally reinforced front doors.
- · Water spray suppression guards and front mudflaps.
- · Laminated windscreen with shade band.
- Two speed windscreen wipers with intermittent wipe mode.
- Halogen multi-reflector headlamps incorporating turn signals and front foglamps. Additional door mounted side indicator lamps.
- Combination brake, turn, reverse and marker lamps, registration plate illumination lamps. Extended wiring harness. Reverse alarm.
- · Roof-mounted clearance lamps.
- Heated and powered exterior main mirrors with flat glass and additional powered convex "spot" mirrors.
- Body coloured grille.
- · Body coloured steel air dam bumper with side cornering lamps.
- FUPD underun bar complies with ECE R93.

## **CAB INTERIOR**

- Isri 6860 air suspension driver's seat with pneumatic lumbar support, height, rake and automatic weight adjustment.
- Front passenger adjustable bucket seat and front centre seat with folding seat back.
- Crew cab: Rear bench seat with 4 seat capacity.
- 3-point lap sash seatbelts in all outboard seating positions. Driver seatbelt
  with pretensioner integrated with driver seat. Outboard front passenger
  seatbelt fitted with pretensioner. Centre seat lap belts.
- Single cab: ADR42 compliant sleeper with mattress.
- · Driver and outboard front passenger airbag.
- Premium Pack: Driver's footrest.
- Door and roof pillar entry assist grips. Crew cab: Full width rear grab rail with ashtray.
- Full interior trim, padded roof lining and vinyl floor covering. Driver and passenger windscreen header storage shelf.
- Tilt/Telescopic adjustable steering column, soft feel urethane steering wheel.
- · Electric windows.
- · Central locking with remote keyless entry and immobiliser.
- Twin cup holders. 24V cigarette lighter. Dashboard hook.
- Front door mounted storage pockets and driver's side ashtray.
- Centre console box with storage tray. Fold down storage tray behind centre seat backrest.
- Fully integrated air conditioning and heater/demister with 4-speed fan and outlets for windscreen, side windows, face and floor. Except single cab Premium Pack: Manual control. Single cab Premium Pack: Auto control.
- Fluorescent type interior lamp with On/Door/Off switch.

- 2 DIN, two speaker radio/CD/DVD Digital Audio Visual Entertainment (DAVE) unit with 6.2" LCD touch screen. DAB+ digital radio and fully integrated Bluetooth with voice recognition. 4GB internal storage for music files. USB/ SD card and auxiliary input connection provisions.
- DIN sized compartment for storage or for CB radio installation.

#### **DRIVER CONTROLS**

- Key-operated engine start/stop and steering lock. Engine idle speed control.
- HSA slow/fast engagement control and on/off switch.
- DPD regeneration.
- Premium Pack: AMT slow/fast gear engagement control, 1st gear start and normal/economy gear selection modes.
- Left side combination stalk: Windscreen wipers, washers and exhaust brake.
- Right side combination stalk: Turn signals, headlamps and cruise control.

#### **INSTRUMENTATION**

- Electronically driven speedometer and tachometer. Digital odometer with integrated dual tripmeter. Engine coolant temperature, fuel level and air pressure gauges.
- Warning lamps: Check engine, oil pressure, ABS, SRS airbag, alternator charge, service brakes, park brake, seatbelt unfastened, low air pressure, low fuel level, cab lock. Premium Pack: Check AMT.
- Indicator lamps: HSA, warm up system, high beam, DPD status, exhaust brake, turn signals, cruise control. Premium Pack: Econo-mode, 1st gear start.
- Premium Pack: Gear selection display.
- Multi-information display. Shows service interval, instantaneous and average fuel consumption, DPD bar chart, hourmeter, voltmeter, time/day/date and includes 40-120 km/h adjustable vehicle speed warning.

## **OPTIONS AND GENUINE ACCESSORIES**

Include the following (extra cost, request a brochure and further details from your Isuzu dealer):

#### **Digital Audio Visual Entertainment unit:**

- Isuzu satellite navigation including three years of free updates.
- Up to four reversing cameras one with audio for reversing. Reversing sensors.
- · Tyre pressure monitoring system.
- Cables for full iPod / iPhone / iPad compatibility and connection to other external audio visual devices.

#### Other:

- · Airbag compatible bullbar.
- Air deflector.

## **ISUZU CARE**

Isuzu Care gives truck owners access to products and services including Roadside Assist, Service Agreements, Extended Care, Extended Isuzu Assist and the Isuzu Care Centre. Call 1800 035 640.








WEIGHTS (kg)								
Models	Ratings*		Loading Limi	t* (at ground)	Cab Chassis Mass #			
Models GVM GCM		GCM	Front	Rear	Front	Rear	Total	
FTR 900 Medium	15,000	24,000**	6,300	9,200	3,130	1,710	4,840	
FTR 900 M-Long	15,000	24,000**	6,300	9,200	3,290	1,750	5,040	
FTR 900 M-Long Premium	15,000	24,000**	6,300	9,200	3,305	1,755	5,060	
FTR 900 Long	15,000	24,000**	6,300	9,200	3,315	1,785	5,100	
FTR 900 Long Premium	15,000	24,000**	6,300	9,200	3,325	1,785	5,110	
FTR 900 Crew	15,000	24,000**	6,300	9,200	3,375	1,885	5,260	
FTR 900 Crew Premium	15,000	24,000**	6,300	9,200	3,385	1,885	5,270	

<sup>\*</sup> Vehicle ratings and front/rear weight limits are subject to government regulatory requirements and weight distribution analysis. Consult your Isuzu dealer to select the correct vehicle for your specific application.
\*\* For tow couplings with a rating over 4,500 kg brake performance matching with trailer is required to ensure compatability under ADR 35/01. # Cab chassis only as supplied and including 10 litres of fuel.

DIMENSIONS (mm)								Turn Circle (m)					
Models	WB	OAL	FOH	ROH	EA	CE	RT	ORT	СН	FFA (unladen)	RFA (unladen)	RFH (unladen)	KERB TO KERB
FTR 900 Medium	4,250	7,405	1,440	1,715	3,550	5,340	1,820	2,430	2,725	945	1,025	1,050	14.1
FTR 900 M-Long	6,050	10,005	1,440	2,515	5,350	7,940	1,820	2,430	2,725	945	1,015	1,050	20.1
FTR 900 Long	6,500	10,740	1,440	2,800	5,800	8,675	1,820	2,430	2,725	935	1,010	1,040	21.6
FTR 900 Crew	6,050	10,005	1,440	2,515	4,625	7,248	1,820	2,430	2,725	935	1,015	1,055	20.1



PERFORMANCE (calculated - typical paved road)							
		Geared Speed* (top gear at peak power engine RPM)	Low Speed Gradeability (lowest forward gear assuming no wheel slip)	Engine Speed (top gear at 100km/h)			
FTR 900	At 15,000kg GVM	106 km/h @ 2,400 RPM	36%	2,275 RPM			

<sup>\*</sup>Maximum speed achievable depends on vehicle frontal area as well as other factors. Consult your Isuzu dealer for more detailed information. Vehicle is speed limited to 100km/h.

ISUZU WARRANTIES				
STANDARD <sup>1</sup>				
New Vehicle	3 years • 150,000km • 2,500 hours			
Cab Perforation Corrosion 3 years • unlimited km's				
Isuzu Assist: 24 hour roadside assistance (3 years, unlimited km's)*				
EXTENDED CARE <sup>2</sup>				
Extended Warranty: 5 years • 300,000km • 5,000 hours				
Isuzu Assist: 24 hour roadside assistance (5 years, unlimited km's)				

UKUEK LUUES					
Model	Code				
FTR 900 Medium	FH-FTRJH-B13				
FTR 900 M-Long	FH-FTRCH-C13				
FTR 900 M-Long Premium	FH-FTRDH-H13				
FTR 900 Long	FH-FTRJH-D13				

Model	Code
FTR 900 Long Premium	FH-FTRKH-Z13
FTR 900 Crew	FH-FTRLH-D13
FTR 900 Crew Premium	FH-FTRMH-C13

1 Subject to the conditions outlined in the IAL New Vehicle Warranty, the Isuzu FTR models carry a standard factory warranty which covers the owner: (i) for the entire vehicle, for the first 36 months or 150,000 km or 2,500 hrs (whichever comes first). (ii) against cab perforation corrosion, for 36 months and unlimited kilometres. Extended Warranty as illustrated may be purchased to cover the owner against the failure of original components, but may exclude some components and expendable items such as oil, filters, etc. Valid for three years from the date of new vehicle purchases. All Isuzu warranties are subject to mandatory prescribed terms under Australian Consumer law including customer guarantees. For more details visit the Isuzu website which explains Isuzu warranties in more detail, or alternatively contact your local dealer. All warranties commence from date of delivery.

ISUZU AUSTRALIA LIMITED ABN 97 006 962 572 ("IAL"). The information in this spec sheet was correct at time of printing, but all measurements, specifications and equipment are subject to change without notice. Some equipment may have been changed and/or is available at extra cost. IAL may make changes at any time without notice, in prices, colours, materials, equipment and models. IAL makes all reasonable attempts to ensure the availability of all vehicles and equipment. The information in this spec sheet is general in nature. Your Isuzu dealer can confirm all measurements, specifications and vehicle / equipment availability upon request. To the extent permitted by the law, IAL is not liable to any person as result of reliance on the content of this spec sheet.





December 2012. ARK0617