



NPR 200 NPR 275



NPR 200 pictured

AUSTRALIA'S TOP SELLING TRUCK BRAND SINCE 1989. Truck tracker 2007.

AT A GLANCE

GVM 4,500 / 5,500 kg **GCM** 8,000 / 9,000 kg **Power** 114 kW @ 2,600 rpm

Torque 419 Nm @ 1,600 - 2,600 rpm

UPGRADE OPTIONS

AMT Pack:

- Automated Manual Transmission (AMT)

Premium Pack:

- Automated Manual Transmission (AMT)
- Instrument panel multi-information display
- Cruise control
- Auto control for airconditioning
- Front foglamps
- Chrome grille

ADVANCED TECHNOLOGY

- Driver and passenger airbag with seatbelt pretensioner
- Anti-lock Braking System (ABS)
- Anti Skid Regulator (ASR)
- Hill Start Aid (HSA) except premium and AMT pack
- Electric mirrors
- Front and rear stabiliser bars

RELIABILITY IS EVERYTHING **SUZU**



Driveline & Chassis Specifications

ENGINE: SITEC SERIES II 155 (ISUZU 4HK1-TCN)

Type: 4 cylinder 16 valve SOHC

Displacement: 5,193 cc **Compression ratio:** 17.5:1

Bore x Stroke: 115 mm x 125 mm

Max power (DIN - NET): 114 kW (153 HP) @ 2,600 RPM

(JIS Gross): 118 kW (158 HP) @ 2,600 RPM

Max torque (DIN - NET): 419 Nm (309 lb.ft) @ 1,600 - 2,600 RPM (JIS Gross): 434 Nm (320 lb.ft) @ 1,600 - 2,600 RPM

air-to-air intercooler.

Fuel injection: Direct injection high pressure common rail system.

Emission control system: Two-stage cooled EGR with exhaust Diesel Particulate Diffuser (DPD). ADR 80/02 (Euro IV) compliant.

CLUTCH

Standard model:

- Auto adjusting hydraulic control with vacuum assistance. Single plate 325 mm diameter.
- Total lining area: 966 cm²

AMT and Premium Pack:

 Fully automated hydraulically controlled wet clutch and fluid coupling with lock up.

TRANSMISSION

Standard model:

ISUZU MYY-5T

- 5 speed manual. Syncromesh on gears 1-5.
- PTO provision on LHS of transmission case. PTO drive from counter gear.

• Gear ratios (: 1)

 1st
 2nd
 3rd
 4th
 5th
 Rev

 5.315
 3.053
 1.655
 1.000
 0.721
 5.068

AMT and Premium Pack:

ISUZU MYY-6S

- 6 speed Automated Manual Transmission (AMT) with both fully automatic and clutchless manual operation modes.
- PTO provision on LHS of transmission case. PTO drive from counter gear.

• Gear ratios (: 1)

 1st
 2nd
 3rd
 4th
 5th
 6th
 Rev

 5.979
 3.434
 1.862
 1.297
 1.000
 0.750
 5.701


AXLES

Front: Isuzu F031

· Reverse Elliot I-beam. 3,100 kg capacity.

Rear: Isuzu R066

- · Full floating Banjo type. Four differential pinions. 6,600 kg capacity.
- Drive ratio: 4.100:1



SUSPENSION

Front:

- · Single stage alloy steel taper leaf springs.
- Double acting hydraulic shock absorbers. Stabiliser bar.

Rear:

- Multi leaf main spring, taper leaf helper spring.
- · Double acting hydraulic shock absorber. Stabiliser bar.

BRAKES

- Auto adjusting front disc and rear drum brakes with dual circuit hydraulic control, vacuum assistance and electronic brake force distribution (EBD).
- · ABS and ASR traction control.
- Hill Start Aid (HSA) except AMT/premium pack.
- Front disc diameter: 293 mm
- Rear drum size: 320 x 100 mm
- 190 mm diameter drum park brake mounted on rear of transmission.
- · Vacuum controlled exhaust brake.

STEERING

- · Power assisted recirculating ball steering.
- Gear ratio: 20.9:1
- Turns lock to lock: 5.4
- Maximum angle: 48° (inside wheel) / 35° (outside wheel)

NPR Short | Medium

WHEELS AND TYRES

- 16 x 5.5.I five stud steel wheels.
- 195/85R16 114/112L Michelin XZA Tubeless.
- · Maximum tyre rating:

Steer axle: 2,360 kg Drive axle: 4,480 kg

· 1 frame mounted spare wheel and tyre assembly.

CHASSIS FRAME

- · Cold rivetted ladder frame. SAPH440 weldable steel sidemembers. Parallel side rails and rivetless top flange.
- · Frame dimensions:

Side rail (mm): 216 x 70 x 6.0 Rear frame width (mm): 850

FUEL TANK

- Frame mounted 100L steel fuel tank.
- · Lockable fuel cap.

ELECTRICAL SYSTEM

- · 24 volt electrical system.
- 80 amp alternator.
- · 4.5 kW starter motor.
- · 2 x 80D26L (630 CCA) batteries connected in series.

Cabin Specifications and Appointments

CAB EXTERIOR

- All steel construction. High tensile steel used for cab underframe. Manual cab tilt to 45° with torsion bar assistance.
- · Liquid filled front and rear cab mounts.
- · Heavy duty non slip entry steps.
- · 90° opening internally reinforced front doors.
- · Water spray suppression guards and front mudflaps.
- · Laminated windscreen with shade band.
- · Two speed windscreen wipers with intermittent wipe mode.
- · Halogen multi-reflector headlamps incorporating turn signals. Additional door mounted side indicator lamps.
- · Combination brake, turn, reverse and marker lamps, registration plate illumination lamps. Extended wiring harness. Reverse alarm.
- · Roof-mounted clearance lamps.
- · Heated and powered exterior main mirrors with flat glass and additional independently adjustable convex "spot" mirrors.
- Except Premium Pack: Body coloured grille. Premium Pack: Chrome grille.
- · Body coloured impact resisting polycarbonate bumper with steel backing frame. Premium Pack: Includes front foglamps.

CAB INTERIOR

- · Contoured adjustable driver's bucket seat.
- · Front passenger bench seat with 2 seat capacity.
- · 3-point lap sash seatbelts in all outboard seating positions. Driver and outboard front passenger seatbelts fitted with pre-tensioner. Centre seat lap belts.
- · Driver and outboard front passenger airbag.
- AMT/Premium Pack: Driver's footrest.
- · Door and roof pillar entry assist grips.
- · Full interior trim, padded roof lining and vinyl floor covering. Driver and passenger windscreen header storage shelf.
- · Tilt/Telescopic adjustable steering column, soft feel urethane steering wheel.
- Electric windows.
- Central locking with remote keyless entry and immobiliser.
- Twin cup holders. 24V cigarette lighter. Dashboard hook.
- · Front door mounted storage pockets and driver's side ashtray.
- · Centre console box with storage tray. Fold down storage tray behind centre seat backrest.

- Fully integrated air conditioning and heater/demister with 4-speed fan and outlets for windscreen, side windows, face and floor. Except Premium Pack: Manual control. Premium Pack: Auto control.
- · Interior lamp with On/Door/Off switch.
- · 2 DIN, two speaker radio/CD multimedia unit.
- . DIN sized compartment for storage or for CB radio installation.

DRIVER CONTROLS

- · Key-operated engine start/stop and steering lock. Engine idle speed control.
- HSA slow/fast engagement control and on/off switch (except AMT/premium pack).
- ASR on/off.
- · DPD regeneration.
- AMT/Premium Pack: AMT slow/fast gear engagement control, 1st gear start and normal/economy gear selection modes.
- · Left side combination stalk: Windscreen wipers, washers and exhaust brake.
- Right side combination stalk: Turn signals and headlamps. Premium Pack: Cruise control.

INSTRUMENTATION

- · Electronically driven speedometer and tachometer. Digital odometer with integrated dual tripmeter. Engine coolant temperature and fuel level gauges.
- · Warning lamps: Check engine, oil pressure, ABS, SRS airbag, alternator charge, service brakes, park brake, seat belt unfastened, low fuel level. AMT/Premium Pack: Check AMT.
- Indicator lamps: HSA (except AMT/premium pack), warm up system, high beam, ASR, DPD status, exhaust brake, turn signals. Premium Pack: Cruise control, econo-mode, 1st gear start.
- . AMT/Premium Pack: Gear selection display.
- Premium Pack: Multi-information display. Shows service interval, instantaneous and average fuel consumption, DPD bar chart, hourmeter, voltmeter, time/day/ date and includes 40-120 km/h adjustable vehicle speed warning.

OPTIONS AND GENUINE ACCESSORIES

Include the following (extra cost, check with dealer for availability):

- · Module for Bluetooth/iPod input/SD card reader.
- · Module for Bluetooth/iPod input/SD card reader/satellite navigation (includes NAVTEQ mapping).
- · Up to two reversing cameras.
- · Airbag compatible bullbar.
- 3,500 kg rated towbar.
- · Cloth seat covers.






Weights (kg) Ratings* Loading Limit* (at ground) Cab Chassis Mass# Models GVM GCM Front Rear Rear Front Total NPR 200 / 275 Short 4,500 / 5,500 8,000 / 9,000 2,360 4,480 1,660 765 2,425 4,500 / 5,500 8,000 / 9,000 4.480 785 2.455 NPR 200 / 275 Medium 2.360 1.670 NPR 200 / 275 Medium AMT 4,500 / 5,500 8,000 / 9,000 2,360 4,480 1,685 825 2,510 4.500 / 5.500 8.000 / 9.000 2.360 4.480 1.690 825 2.515 NPR 200 / 275 Medium Premium

Maximum Gross Trailer Mass: 750 kg (unbraked), 3,500 kg (braked) * Vehicle ratings and front/rear weight limits are subject to government regulatory requirements and weight distribution analysis. Consult your Isuzu dealer to select the correct vehicle for your specific application. # Cab chassis only as supplied and including 10 litres of fuel.

Dimensions (mm)									Turn Circle (m)				
Models	WB	0AL	FOH	R0H	EA	CE	RT	ORT	СН	FFA (unladen)	RFA (unladen)	RFH (unladen)	KERB TO KERB
NPR 200 / 275 Short	2,765	5,385	1,110	1,510	2,080	3,702	1,650	2,080	2,260	635	745	790	9.6
NPR 200 / 275 Medium	3,365	5,985	1,110	1,510	2,680	4,302	1,650	2,080	2,260	640	750	785	11.7



Performance (calculated - typical paved road)							
		Geared Speed* (top gear at peak power engine RPM)	Low Speed Gradeability (lowest forward gear assuming no wheel slip)	Engine Speed (top gear at 100 km/h)			
NPR 200	At 4,500 kg GVM	119 km/h @ 2,600 RPM	52%	2,190 RPM			
NPR 200 AMT / Premium Pack	At 4,500 kg GVM	114 km/h @ 2,600 RPM	58%	2,275 RPM			
NPR 275	At 5,500 kg GVM	119 km/h @ 2,600 RPM	42%	2,190 RPM			
NPR 275 AMT / Premium Pack	At 5,500 kg GVM	114 km/h @ 2,600 RPM	47%	2,275 RPM			

^{*} Maximum speed achievable depends on vehicle frontal area as well as other factors. Consult your Isuzu dealer for more detailed information

Isuzu Warranties							
STANDARD ¹							
New Vehicle	3 years 100,000 km 2,000 hrs						
Cab Perforation Corrosion	3 years Unlimited km						
EXTENDED ²							
4 years 200,000 km	5 years 250,000 km	6 years 300,000 km					

Order Codes						
Code	Model	Code				
NH-NPRCB-A01	NPR 200 / 275 Medium AMT	NH-NPRCB-F01				
NH-NPRCB-B01	NPR 200 / 275 Medium Premium	NH-NPRDB-F01				
	Code NH-NPRCB-A01	Code Model				

¹ Subject to the conditions outlined in the IAL. New Vehicle Warranty, the Isuzu NPR models carry a standard factory warranty which covers the owner: (i) for the entire vehicle, for the first 36 months or 100,000 km or 2,000 hrs (whichever comes first). (ii) against cab perforation corrosion, for 36 months and unlimited kilometres. 2 Extended Warranty as illustrated is available by purchase to cover the owner against the failure of original components, but may exclude some components and expendable items such as oil, filters, etc. Please consult with your Isuzu Dealer for full details obtained from a dedicated brochure available to customers

ISUZU AUSTRALIA LIMITED ABN 97 006 962 572 ("IAL"). The information in this brochure was correct at time of printing, but all measurements, specifications and equipment are subject to change without notice. Some equipment may have been changed and/or is available at extra cost. IAL may make changes at any time without notice, in prices, colours, materials, equipment and models. IAL makes all reasonable attempts to ensure the availability of all vehicles and equipment. The information in this brochure is general in nature. Your Isuzu dealer can confirm all measurements, specifications and vehicle / equipment availability upon request.

July 2008 ARK0324

