

ISUZU TRUCK SPECIFICATIONS

NKR TIPPER

4 x 2 CAB/CHASSIS NKR/NPR SHORT

MODEL: NKR200 Short
ORDERING CODE: 8CL02-11T

NKR 200 SHORT



Engine:	4BE1, 3.6L, 4cyl Direct injection diesel.	GVM:	4490kg
Power:	74kW @ 3500 rpm (DIN Nett)	GCM:	6490kg
Torque:	242 Nm @ 2000 rpm (DIN Nett)	Kerb mass: (incl body)	1850kg 2600kg
Transmission:	MSA5G 5 speed overdrive.	Wheel base:	2460mm
Clutch:	Hydraulic Control, dry Single plate.	Cab to axle:	1890mm
Suspension:	Front/rear Semi elliptical alloy steel leaf springs. Hydraulic, double acting shock absorbers.	Frame width:	700mm
Brakes:	Hydraulic, dual circuit, with vacuum servo.	Front track:	1385mm
Cab:	All steel, tilt cab Driver's seat: adjustable, reclining, bucket. 2 Passenger seat, cloth trim.	Rear track:	1425mm
		Turning circle:	11.0m (Kerb to kerb)
		Warranty:	12 months, 20,000 kilometres



ISUZU - RELIABILITY IS EVERYTHING

BODY SPECIFICATIONS (NKR TIPPER)



1. GENERAL

Body dimensions

- Internal 2700mm long x 1930mm wide x 290mm high.

Body volume

- 1.5 cubic metre

Body tare (incl fittings)

- 750kg

Floor height above chassis

- 209mm

Angle of tip

- 50 degrees

Rate of tip

- 37 sec at 1000 rpm

2. HYDRAULICS

Hoist make

- Hoist hydraulics

Hoist model

- EMU 3013-93183

Hoist capacity

- 5 tonne.

Hoist stroke

- 1050mm 4 stage operation.

Hoist mounting

- Underbody telescopic

Hoist operator controls

- Cabin located cable to control valve and P.T.O. with dash mounted warning light indicating P.T.O engagement.

Operator warning instructions

- As supplied by Powauto on Dash and sun-visor.

PTO pump combination

- Directly coupled to MSA5G Transmission
- Powauto H360SBR14, MK411, CK3518, A6SP0350, CF59, 38045 elbow. Operating pressure 210MPA
- Flow 14LT/per minute.
- Control Valve

3. CHASSIS SUBFRAME

Bearers

- 102 x 51 x 3.2 RHS fitted to chassis by 2 of 150 x 10 flitch plates per side.

Hoist mounting

- 76 x 51 x 4 RHS crossmember with 75 x 50 x 8mm angle hoist mounts.

4. BODY

Cabguard

- Up to height of cabin with small fold with central mesh covered rear vision aperture with pressed front rail 3mm material.

Floor - Bearers and frame

- 102 x 51 x 3.2 RHS longmembers. Side coaming 76 x 51 x 3.2 RHS. Rear coaming of 102 x 51 x 3.2 RHS.

Floor - Material

- One piece 5mm AS1204 grade 250 with press formed side coaming.

Rope rails

- 20mm pipe on sides cut out over wheels.

Sides

- Monopanel 2mm AS1204 grade 250 presses to Hercules design and fully welded and sealed.

Tailgate

- Drop side operation with standard catches and bottom hinged external to side coaming.

Fittings

- Monopanel 2mm AS1204 grade 250 pressed to Hercules design and fully welded and sealed.
- Tophinged double acting with manual opening and closing mechanism of R.H.S. of body.
- Shovel rack
- Access step ladder and handgrip
- Body safety prop
- Rear lights
- Isuzu mudflaps front and rear.

Warranty: Material and workmanship. Twelve months, 20,000km.



ISUZU - RELIABILITY IS EVERYTHING

RGS CT374 APRIL 1990