


# 800

**FTR 800 MEDIUM**


**GVM: 13,900kg**  
**GCM: 20,400kg**  
**WHEELBASE: 4,200mm**

## ISUZU 6HE1 ENGINE PERFORMANCE




- Type: 6 cylinder overhead camshaft diesel, four stroke, direct injection
- Bore x Stroke 110 x 125 mm
- Displacement 7127 cc
- Compression Ratio 17.0:1
- Output-Power 129 kW @ 2870 rpm (DIN Nett)
- Torque 471 Nm @ 1800 rpm (DIN Nett)

## DIMENSIONS AND WEIGHTS



*ESTIMATED KERB MASS (kg)	
FRONT	2574
REAR	1766
TOTAL	4340
FRAME WIDTH (mm)	
	850
TURNING CIRCLE (m)	
Kerb to Kerb	14.4
BODY LENGTH (mm)	
	5480
Subject to weight distribution	



\*Chassis and cab with oil, water and fuel tank containing 10 litres of fuel.

ISUZU-GENERAL MOTORS AUSTRALIA LTD A.C.N. 006 962 572

12/50 WARRANTY. Every Isuzu Truck is covered by the I-GM new vehicle warranty which covers your vehicle for the first 12 months or 50,000 kilometres.

PLEASE NOTE: as the policy of Isuzu-General Motors Australia Limited is one of continual product improvement, all specifications and equipment are subject to change without notice. Body illustrated are not standard. No I-GM dealer or other person is authorised to give or make any statement, assertion or undertaking in relation to the quality performance characteristics descriptions or fitness for any purpose of any I-GM product or in connection with the supply of any I-GM product which is at variance with any written statement assertion or undertaking on any of these subjects given or made by Isuzu-General Motors Australia Limited in its published sales literature, and the company accepts no liability for any such unauthorised action. Isuzu-General Motors Australia Limited has franchised dealers in many parts of Australia. For the sale of service parts and the provision of service to owners of I-GM products. Every endeavour is made to ensure that such dealers carry adequate stocks of service parts, and are equipped to provide satisfactory service, but makes no promise, other than that contained in the New Vehicle Warranty given by Isuzu-General Motors Australia Limited, that such parts or service facilities will be available, or available at any specific location or any particular time.

CT4242-4/93

ISUZU







# 800

FTR 800 MEDIUM

**ORDERING CODE:**  
**8FL02-411**

## ENGINE - ISUZU 6HE1

### Lubrication:

- Pressure feed lubrication with full flow paper element and partial flow sub filter. Plate type oil cooler in water jacket. Oil capacity 15 litres including filter.

### Cooling System:

- Six blade plastic cooling fan, size 470 mm diameter with thermatic fan clutch.
- Tube and corrugated fin pressure type radiator with bell mouth fan shroud. Size (mm) 622 h x 559 w x 52 t. Frontal area 0.348 m<sup>2</sup>.
- Coolant capacity 25 litres.

## FUEL SYSTEM

- Two stage paper element air cleaner, Donaldson 11" with vertical air intake stack and rain head.
- In line plunger, Bosch 'A' type fuel injection pump with mechanical all speed governor.
- In line paper filter, see through water separator with drain cock.
- Fuel tank capacity 200 litres.
- Horizontal exhaust muffler with vertical exhaust stack.

## CLUTCH

- Hydraulic control dry single plate with coil type cushioning springs. 350 mm (14") diameter.
- Asbestos free lining material. Total swept area (both sides) 1054cm<sup>2</sup>.

## TRANSMISSION ISUZU MLD7R

- Seven speed overdrive, constant mesh with synchromesh on gears 2-7, power assisted shift control, oil capacity 8.3 litres.
- Gear Ratios:1
  - 1st 8.181
  - 2nd 5.167
  - 3rd 3.333
  - 4th 2.105
  - 5th 1.347
  - 6th 1.000
  - 7th 0.863
  - Reverse 8.307
- Maximum geared speed 99.6 km/h.
- Two piece propeller shaft, 90 mm diameter  
Length: 1st section 713 mm  
2nd section 1292.5 mm

## REAR AXLE - R092 CAPACITY 9,200kg

- Banjo type, fully floating, single reduction. Ratio 6.143:1
- Hypoid type ring gear, 398 mm diameter  
Oil capacity 8 litres

## REAR SUSPENSION

- Semi-elliptical, alloy steel tapered multi-leaf springs. Fully wrapped eye with greasable shackles.

- Size: length - width x thickness, No leaves  
Main: 1420 - 80 x 12 mm, 1 leaf  
80 x 13 mm, 6 leaves  
Auxiliary: 1000 - 80 x 13 mm, 4 leaves  
80 x 12 mm, 2 leaves
- Stabiliser bar.

## FRONT AXLE - F063 CAPACITY 6,300KG

- Reverse Elliot I-beam type, king pin diameter 50 mm with cylindrical roller thrust bearing.

## FRONT SUSPENSION

- Semi-elliptical, alloy steel parabolic taper leaf springs. Fully wrapped eye with greasable shackles.
- Size: length - width x thickness, No leaves  
1470 - 80 x 19 mm, 1 leaf  
80 x 21 mm, 2 leaves
- Stabiliser bar
- Hydraulic, double acting, telescopic shock absorbers.

## STEERING

- Fully integral power assisted recirculating ball type. Gear ratio 22.4:1. Turns lock to lock 5.4.
- Gear driven vane type oil pump, oil capacity 3.5 litres.

## BRAKES

- Air over hydraulic dual circuit, front two leading, rear dual two leading. Drum diameter front and rear 410 mm. Total swept area 7209.4 cm<sup>2</sup>.
- Spring park brake acting on rear wheels.
- Butterfly, air controlled exhaust brake system. Activation switch on wiper/washer control stalk.

## CHASSIS FRAME

- Parallel rail, ladder type, channel section cold rivetted.
- Side member dimensions 253 x 80 x 7.5 mm
- Frame reinforcement angle section 224 x 72.5 x 4.5 mm at back of cab.
- Material SAPH45 mild steel.

## WHEELS AND TYRES

- 7.00T x 20 - 10 stud disc wheels 22 mm bolt size. 162 mm offset.
- 9.00 R 20 - 14 ply radial tyres, front and rear.
- Number of tyres, 7 including spare.
- Winch type spare wheel carrier.

## ELECTRICAL SYSTEM

- Batteries - 2 x 12 volt - 55 amp/h, negative earth.
- Alternator - 24 volt - 40 amp.
- Starter motor - 24 volt - 4.5 kW output.
- Rear stop and tail lamps and licence plate lamp with long leads for variable body mounting. Turn signal side indicator lamps for body mounting.

## CAB EXTERIOR

- All steel cab, manual tilt to 45°, cation electro deposition primer. Torsion bar counter balanced with silicon sealed hydraulic mountings.
- Heavy duty bumper bar with four rectangular halogen headlamps inset.
- Combination turn signal and park lamps.
- Tinted laminated windshield, 2 speed wiper/washer with intermittent mode.
- Tinted quarter vent, side and rear glass.
- West Coast type rear view mirrors with clearance lamps.
- Corrosion resistant non slip cab entry steps.
- Access to engine fluid checks without tilting cab.
- Tool kit with 10,000 kg capacity jack.

## CAB INTERIOR

- Fully trimmed cab interior with two tone cloth seat facings, formed roof lining and overhead parcel shelf with driver and passenger sun visors.
- ISRI 6000 drivers seat with mechanical suspension and lumbar support, adjustment for seat back recline, seat slide and height control.
- Outboard reclining passenger seat, folding centre seat back with lockable compartment and snack tray.
- Outboard lap/sash seat belts with emergency locking retractors inboard lap seat belt.
- Tilt telescopic adjustable steering column, soft feel urethane steering wheel.
- Easy entry grab handles on 'A' and 'B' pillars.
- Heater demister with 4 speed fan, 4 outlets to screen 5 fascia outlets, 5 foot outlets.
- AM/FM radio with digital clock, dash mounted.

## INSTRUMENTATION

- Speedometer, odometer, and tachometer.
- Gauges for coolant temperature, fuel level and brake air pressure.
- Dash illumination control.

## INDICATOR LAMPS

- Turn signals, parking brake on, high beam on, exhaust brake engaged, brake fluid level.

## WARNING LAMPS

- With warning bulb check switch.
- Battery charge, oil filter clogged, oil pressure. Low air pressure, brake system, air cleaner clogged stop and tail lamp failure.

## SWITCHES

- Left side combination switch for exhaust brake, wipers and washer.
- Right side combination switch for headlamps, turn signals and headlamp dip.
- Hazard lamp switch.
- Key operation for engine stop and start external engine crank switch for service when cab is tilted.
- Three way switch for interior lamp activated by driver and passenger doors.
- 24 volt 2 pin accessory plug on centre fascia panel.